



PRODUCT DATA SHEET

OP - 2PORT

- 2 PORT MOTORISED VALVE
- 22mm COMPRESSION FITTINGS
- END SWITCH
- REPLACEABLE ACTUATOR
- MANUAL / AUTO LEVER



OP-2PORT IS A 2-PORT MOTORISED VALVE, SUPPLIED WITH 22MM COMPRESSION FITTINGS, FOR FLOW CONTROL OF CENTRAL HEATING OR HOT WATER IN 'S PLAN' CENTRAL HEATING SYSTEMS. THE VALVE OPERATES IN CONJUNCTION WITH EITHER A ROOM OR CYLINDER THERMOSTAT; OPENING ON THERMOSTAT DEMAND SIGNAL BY THE ACTION OF A GEARED SYNCHRONOUS MOTOR, AND CLOSING BY A SPRING RETURN MECHANISM. WHEN OPENED A LIMIT SWITCH OPERATES TO SWITCH ON THE HEAT SOURCE. MUST BE INSTALLED ACCORDING TO THE DIRECTION OF FLOW AS INDICATED BY THE ARROW ON THE VALVE BODY. ONLY SUITABLE FOR OPEN VENTED OR SEALED PUMPED SYSTEMS

CONNECTION	5 CORE COLOUR CODED FLEXIBLE CABLE 1 METRE
POWER CONSUMPTION	6W
TEMPERATURE RANGE	5 TO 88°C
MAX DIFFERENTIAL PRESSURE	1 BAR
MAX STATIC PRESSURE	10 BAR
MAX FLUID TEMPERATURE	100 °C
MANUAL LEVER	YES
REPLACEABLE ACTUATOR HEAD	YES
REPLACEABLE MOTOR	YES

